

MoviSight

A1. Model No.:	A2. Product Name:																																														
MS-7FHD135639CAI	HD CAMERA																																														
B1. Product Keywords:																																															
<ol style="list-style-type: none"> 1) IP ONVIF /RTSP 1080P 30 FPS 2) Waterproof: IP69K approved 3) Super wide viewing angle: 130° 4) Smart-IR 5) Mirror / Normal image switch 																																															
B2. Product Features:																																															
<ol style="list-style-type: none"> 1) Nightvision distance: 15 m (4 infrared lights) 2) Day / Night sensor for automatic adjustment 																																															
B3. Key Specifications:																																															
<table border="0"> <tr><td>Image Device:</td><td>1/2.9" CMOS</td></tr> <tr><td>Frame Rate:</td><td>25fps / 30fps</td></tr> <tr><td>Effective Pixels:</td><td>1920 (H) x 1080 (V)</td></tr> <tr><td>Pixel pitch</td><td>2.9 μm x 2.9 μm</td></tr> <tr><td>Scanning System:</td><td>Progressive Scanning</td></tr> <tr><td>Sync. System:</td><td>Internal</td></tr> <tr><td>Resolution:</td><td>1080P</td></tr> <tr><td>Minimum Illumination:</td><td>0.1 Lux (day), 0 Lux (with IR)</td></tr> <tr><td>Microphone:</td><td>Yes</td></tr> <tr><td>Video Output:</td><td>1.0Vp-p, 75Ohm</td></tr> <tr><td>Gamma Consumption:</td><td>0.45</td></tr> <tr><td>AGC:</td><td>Auto</td></tr> <tr><td>Dynamic range:</td><td>Better than 81dB</td></tr> <tr><td>White Balance:</td><td>Auto</td></tr> <tr><td>Electronic Shutter:</td><td>1/30 (1/25) ~ 1/50,000 Seconds</td></tr> <tr><td>BLC:</td><td>Auto</td></tr> <tr><td>Current Consumption:</td><td>Max. 250mA</td></tr> <tr><td>Power Supply:</td><td>DC12V / IEEE 802.3af POE</td></tr> <tr><td>Connection:</td><td>RCA / 4 PIN</td></tr> <tr><td>Anti-vibration:</td><td>5.9G</td></tr> <tr><td>Operating Temperature:</td><td>-20°C~70°C, RH 95% MAX.</td></tr> <tr><td>Lens:</td><td>f = 6mm/3.6 mm / 2.8 mm</td></tr> <tr><td>Lens Angle:</td><td>70°/110°/130°</td></tr> </table>	Image Device:	1/2.9" CMOS	Frame Rate:	25fps / 30fps	Effective Pixels:	1920 (H) x 1080 (V)	Pixel pitch	2.9 μm x 2.9 μm	Scanning System:	Progressive Scanning	Sync. System:	Internal	Resolution:	1080P	Minimum Illumination:	0.1 Lux (day), 0 Lux (with IR)	Microphone:	Yes	Video Output:	1.0Vp-p, 75Ohm	Gamma Consumption:	0.45	AGC:	Auto	Dynamic range:	Better than 81dB	White Balance:	Auto	Electronic Shutter:	1/30 (1/25) ~ 1/50,000 Seconds	BLC:	Auto	Current Consumption:	Max. 250mA	Power Supply:	DC12V / IEEE 802.3af POE	Connection:	RCA / 4 PIN	Anti-vibration:	5.9G	Operating Temperature:	-20°C~70°C, RH 95% MAX.	Lens:	f = 6mm/3.6 mm / 2.8 mm	Lens Angle:	70°/110°/130°	
Image Device:	1/2.9" CMOS																																														
Frame Rate:	25fps / 30fps																																														
Effective Pixels:	1920 (H) x 1080 (V)																																														
Pixel pitch	2.9 μm x 2.9 μm																																														
Scanning System:	Progressive Scanning																																														
Sync. System:	Internal																																														
Resolution:	1080P																																														
Minimum Illumination:	0.1 Lux (day), 0 Lux (with IR)																																														
Microphone:	Yes																																														
Video Output:	1.0Vp-p, 75Ohm																																														
Gamma Consumption:	0.45																																														
AGC:	Auto																																														
Dynamic range:	Better than 81dB																																														
White Balance:	Auto																																														
Electronic Shutter:	1/30 (1/25) ~ 1/50,000 Seconds																																														
BLC:	Auto																																														
Current Consumption:	Max. 250mA																																														
Power Supply:	DC12V / IEEE 802.3af POE																																														
Connection:	RCA / 4 PIN																																														
Anti-vibration:	5.9G																																														
Operating Temperature:	-20°C~70°C, RH 95% MAX.																																														
Lens:	f = 6mm/3.6 mm / 2.8 mm																																														
Lens Angle:	70°/110°/130°																																														
C1. Accessories:																																															
<ol style="list-style-type: none"> 1- Manual 1- Screwdriver 																																															