

MoviSight

A1. Model No.: MS-7BV060A17	A2. Product Name: 2D/ 3D 360°AROUND-VIEW SYSTEM	
B1. Product Keywords: 1) 04 AHD video inputs 2) Techniques of quad-core ARM Cortex-A53 and SOC development of built-in high-performance H.264 video encoding/decoding engineer core make it efficient to composite seamless images with high accuracy. 3) Support 2 pcs 128G SD card as video media. 4) Low-cost calibration tools, simplified calibration procedures. 5) Max 4CH 1080P/30fps or 4CH 1080P/25fps resolution. 6) High definition 1080P video output. 7) Single-step calibration for built-in and peripherals parameters of cameras, no need to bound the cameras and the main unit.		
B2. Key Specifications:		
Image Processing Unit:		
Language: Video Input: Video Output: TV System: Trigger Input: Signal Output: Viewing Angle Operating Voltage: Operating Current: Operating Temperature: Storage Temperature: Operating Humidity:	English Max.4CH×1080P AHD (25/30)FPS 1-CH 1080P HDMI or AHD/ CVBS(D1) / RTP/ RTSP PAL / NTSC 1-CH backward line trigger,1-CH turn left trigger, 1-CH turn right trigger, 1-CH reserved trigger 1-CH reserved signal output Horizontal: >190° ; Vertical: >130° 10-32V <2A/12V -20℃-70℃ -40℃-105℃ 10% - 95%	
Camera:		
Image Device: Frame Rate: Effective Pixels: Resolution: Nightvision Distance: Minimum Illumination: Video Output: Operating Voltage: Operating Current: Operating Temperature: Storage Temperature: IP Rating:	1/2.9" CMOS 25fps / 30fps 1920(H) x1080 (V) / 1280(H)x720 (V) 1080P / 720P 3-5m (Starlight level,Visible when <0.1 lux) 0.1 Lux (day), 0 Lux (with IR) 1.0Vp-p, 75Ω 12V <140mA DC 12V -20℃-70℃, RH95%MAX. -40℃-105℃, RH95%MAX. IP69K	
C1. Accessories:		
1- IR extension cable 1- Remote control 2- Tapes	1- Main harness for connection of cameras 4- 20m camera connection cables 4- Screws(One screw per camera)	1- Power cable of control box 1- Manual 1- Hex wrench