

MoviSight®

MS-7CC75NKB

Network Control Keyboard



Key Feature

- Network control with independent IP address
- Support ONVIF
- 5 inch industrial LCD screen, resolution 1280 × 720
- Supports up to 1080P@60fps video decoding
- 4D joystick control PTZ function
- Supports up to 254 devices and presets
- Supports exposure, white balance, zoom control, and multi-speed joystick

Specification

General	
Operating System	Linux
Screen Size	5-inch LCD
Display Resolution	1280 × 720
Decoding Capability	H.264 / H.265
Max Decoding Capability	1080p@60fps
Protocol	Supports ONVIF 2.8
Function	<ul style="list-style-type: none">- Supports up to 254 device additions- Supports preset positions- Supports exposure control- Supports white balance control- Independent zoom control- Multi-speed joystick control
System Settings	Supports language settings, firmware upgrade, MAC address binding
Interface	<ul style="list-style-type: none">- 1× RJ45 (Network / PoE)- RS485/RS422 (Terminal block)- RS232 (DB9)
Power Supply	DC 12V ±10% / PoE
Power Consumption	<1.5W
Operating Temperature	-10 °C to 50 °C (14 °F to 122 °F)
Operating Humidity	10% to 90% RH (non-condensing)
Storage Temperature	-40 °C to 60 °C (-40 °F to 140 °F)
Product Dimensions (W × D × H)	297 × 210 × 123.5 mm (11.7 × 8.3 × 4.86 inch)
Net Weight	Approx. 1375 g (3.03 lb)

Dimensions (mm)

